



- Non-woven fabric in PP
- Acrylic glue
- Silicone liner



**Description and use:** professional adhesive tape in nonwoven fabric of polypropylene with highly adhesive acrylic glue, for external or internal use. It is specially designed for air and wind-tight sealing of critical points of the building envelope which need a following fine or rough plastering. Particularly indicated for the connection of wood structures to walls which will be plastered, for joining insulation to building structures (wood, masonry, cement), for covering traces in walls for the installation of cables or pipes, or in the area of frames for sealing conjunction of subframes and walls.

**Application:** identify the surfaces to be bonded and make sure that they are dry and free from dust and grease (alternatively, use USB Primer to treat the surfaces); after cutting the strip to the desired length, remove the protective liner and apply the adhesive strip to the overlap of the required surfaces and press firmly along the entire adhesive tape using the roller so that the adhesive bonds properly. At this point, the tape is ready to be plastered over.

## QUICK OVERVIEW: STRENGTHS

### The plasterable one!

Adhesive tape in **nonwoven fabric** that can be **plastered** over for interior and exterior use.

**High-performance** acrylic glue, solvent free.

Ideal for connection of structures in wood with structures to be plastered.

### Easy and quick application.



Technical data sheet	
Measurements	50 mm x 25 m
Colour	grey
Glue	dispersion based acrylic solvent and plasticiser free
Thickness	0,55 - 0,60 mm
Glue weight	240 g/m <sup>2</sup> ± 10%
Glue carrier material	Non-woven fabric in PP
Covering material	silicone liner
Peel adhesion (AFERA 5001)	≥ 30 N/25 mm
Tear resistance with elasticity	≥ 50 N/25 mm; 40%
Sd value	ca. 9 m
Recommended working temperature	from +5°C
Working temperature (workable)	from -10°C
Operating temperature	from -30°C to +100°C
Adhesion reaction time	immediate / maximum adhesion in 24 h
UV stability	3 months
Packaging	boxes of 12 rolls (12 x 25 m)
Storage	keep in a cool and dry place for max. 24 months

Riwega Srl is not responsible for negligent or improper use of its products.